



STANDARD PACKAGING - Surethread Standard and Extra Heavy Pipe

| A53 Type F Sch. 40 Black P.E. | | | | | A53 Type F Sch. 40 Black T & C | | | | | A53 Type F Sch. 40 Galvanized P.E. | | | | | A53 Type F Sch. 40 Galvanized T&C | | | | |
|-------------------------------|---------|---------------|--------|---------------|--------------------------------|---------|---------------|--------|---------------|------------------------------------|---------|---------------|--------|---------------|-----------------------------------|---------|---------------|--------|---------------|
| NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft - 21' | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft - 21' | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft - 21' | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft - 21' |
| 1/2 | 00055 | 127 | 0.85 | 2667 | 1/2 | 00467 | 127 | 0.85 | 2667 | 1/2 | 00144 | 127 | 0.85 | 2667 | 1/2 | 00557 | 127 | 0.85 | 2667 |
| 3/4 | 00056 | 91 | 1.13 | 1911 | 3/4 | 00468 | 91 | 1.13 | 1911 | 3/4 | 00145 | 91 | 1.13 | 1911 | 3/4 | 00558 | 91 | 1.13 | 1911 |
| 1 | 00057 | 70 | 1.68 | 1470 | 1 | 00469 | 70 | 1.68 | 1470 | 1 | 00146 | 70 | 1.68 | 1470 | 1 | 00559 | 70 | 1.68 | 1470 |
| 1-1/4 | 00058 | 51 | 2.27 | 1071 | 1-1/4 | 00470 | 51 | 2.28 | 1071 | 1-1/4 | 00147 | 51 | 2.27 | 1071 | 1-1/4 | 00560 | 51 | 2.28 | 1071 |
| 1-1/2 | 00059 | 44 | 2.72 | 924 | 1-1/2 | 00471 | 44 | 2.73 | 924 | 1-1/2 | 00148 | 44 | 2.72 | 924 | 1-1/2 | 00561 | 44 | 2.73 | 924 |
| 2 | 00060 | 30 | 3.66 | 630 | 2 | 00472 | 30 | 3.68 | 630 | 2 | 00149 | 30 | 3.66 | 630 | 2 | 00562 | 30 | 3.68 | 630 |
| 2-1/2 | 00061 | 20 | 5.80 | 420 | 2-1/2 | 00473 | 20 | 5.82 | 420 | 2-1/2 | 00150 | 20 | 5.80 | 420 | 2-1/2 | 00563 | 20 | 5.82 | 420 |
| 3 | 00062 | 13 | 7.58 | 273 | 3 | 00474 | 13 | 7.62 | 273 | 3 | 00151 | 13 | 7.58 | 273 | 3 | 00564 | 13 | 7.62 | 273 |
| 3-1/2 | 00063 | 10 | 9.11 | 210 | | | | | | 3-1/2 | 00152 | 10 | 9.11 | 210 | | | | | |
| 4 | 00064 | 10 | 10.80 | 210 | 4 | 00476 | 10 | 10.89 | 210 | 4 | 00153 | 10 | 10.80 | 210 | 4 | 00566 | 10 | 10.89 | 210 |

| A53 Type F Sch. 80 Black P.E. | | | | | A53 Type F Sch. 80 Black T&C | | | | | A53 Type F Sch. 80 Galvanized P.E. | | | | | A53 Type F Sch. 80 Galvanized T&C | | | | |
|-------------------------------|---------|---------------|--------|---------------|------------------------------|---------|---------------|--------|---------------|------------------------------------|---------|---------------|--------|---------------|-----------------------------------|---------|---------------|--------|---------------|
| NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft - 21' | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft - 21' | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft - 21' | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft - 21' |
| 1/2 | 02187 | 91 | 1.09 | 1911 | 1/2 | 02404 | 91 | 1.09 | 1911 | 1/2 | 02276 | 91 | 1.09 | 1911 | 1/2 | 02493 | 91 | 1.09 | 1911 |
| 3/4 | 02188 | 79 | 1.47 | 1659 | 3/4 | 02405 | 79 | 1.48 | 1659 | 3/4 | 02277 | 79 | 1.47 | 1659 | 3/4 | 02494 | 79 | 1.48 | 1659 |
| 1 | 02189 | 44 | 2.17 | 924 | 1 | 02406 | 44 | 2.18 | 924 | 1 | 02278 | 44 | 2.17 | 924 | 1 | 02495 | 44 | 2.18 | 924 |
| 1-1/4 | 02190 | 34 | 3.00 | 714 | 1-1/4 | 02407 | 34 | 3.02 | 714 | 1-1/4 | 02279 | 34 | 3.00 | 714 | 1-1/4 | 02496 | 34 | 3.02 | 714 |
| 1-1/2 | 02191 | 29 | 3.63 | 609 | 1-1/2 | 02408 | 29 | 3.66 | 609 | 1-1/2 | 02280 | 29 | 3.63 | 609 | 1-1/2 | 02497 | 29 | 3.66 | 609 |
| 2 | 02192 | 19 | 5.02 | 399 | 2 | 02409 | 19 | 5.07 | 399 | 2 | 02281 | 19 | 5.02 | 399 | 2 | 02498 | 19 | 5.07 | 399 |
| 2-1/2 | 02193 | 13 | 7.66 | 273 | 2-1/2 | 02410 | 13 | 7.73 | 273 | 2-1/2 | 02282 | 13 | 7.66 | 273 | 2-1/2 | 02499 | 13 | 7.73 | 273 |
| 3 | 02194 | 10 | 10.25 | 210 | 3 | 02411 | 10 | 10.33 | 210 | 3 | 02283 | 10 | 10.25 | 210 | 3 | 02500 | 10 | 10.33 | 210 |

| A53 Type F Sch. 40 Black TBE - 10' | | | | | A53 Type F Sch. 40 Galvanized TBE - 10' | | | | | ** Yellow Indicates "Special -to be inquired" Any length other than 21' to be inquired with your Customer Service Rep. for availability & minimum order requirement. | | | | | | | | | |
|------------------------------------|---------|---------------|--------|---------|---|---------|---------------|--------|---------|--|--|--|--|--|--|--|--|--|--|
| NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft | | | | | | | | | | |
| 1/2 | 00251 | 127 | 0.85 | 1270 | 1/2 | 00403 | 127 | 0.85 | 1270 | | | | | | | | | | |
| 3/4 | 00252 | 91 | 1.13 | 910 | 3/4 | 00404 | 91 | 1.13 | 910 | | | | | | | | | | |
| 1 | 00253 | 70 | 1.68 | 700 | 1 | 00405 | 70 | 1.68 | 700 | | | | | | | | | | |
| 1-1/4 | 00254 | 51 | 2.27 | 510 | 1-1/4 | 00406 | 51 | 2.27 | 510 | | | | | | | | | | |
| 1-1/2 | 00255 | 44 | 2.72 | 440 | 1-1/2 | 00407 | 44 | 2.72 | 440 | | | | | | | | | | |
| 2 | 00256 | 30 | 3.65 | 300 | 2 | 00408 | 30 | 3.65 | 300 | | | | | | | | | | |
| 2-1/2 | 00257 | 20 | 5.79 | 200 | 2-1/2 | 00409 | 20 | 5.79 | 200 | | | | | | | | | | |
| 3 | 00258 | 13 | 7.58 | 130 | 3 | 00410 | 13 | 7.58 | 130 | | | | | | | | | | |
| 4 | 00260 | 10 | 10.79 | 100 | 4 | 00412 | 10 | 10.79 | 100 | | | | | | | | | | |

STANDARD PACKAGING - ERW AND SPRINKLER PIPE

| A53 Type E -Grade B Sch. 40 ERW Black P.E. | | | | | A53 Type E -Grade B Sch. 40 ERW Black R.G. | | | | | A53 Type E Grade B Sch. 40 ERW Galvanized P.E. | | | | | A53 Type E Grade B Sch. 40 ERW Galvanized R.G. | | | | |
|---|---------|---------------|--------|---------------|---|---------|---------------|--------|---------------|---|---------|---------------|--------|---------------|---|---------|---------------|--------|---------------|
| NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft - 21' | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft - 21' | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft - 21' | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft - 21' |
| 2.375 | 01248 | 24 | 3.66 | 504 | 2.375 | 11248 | 24 | 3.66 | 504 | 2.375 | 70645 | 24 | 3.66 | 504 | 2.375 | 11330 | 24 | 3.66 | 504 |
| 2.875 | 01249 | 20 | 5.80 | 420 | 2.875 | 11267 | 20 | 5.80 | 420 | 2.875 | 01287 | 20 | 5.80 | 420 | 2.875 | 11331 | 20 | 5.80 | 420 |
| 3.500 | 01250 | 13 | 7.58 | 273 | 3.500 | 11268 | 13 | 7.58 | 273 | 3.500 | 01323 | 13 | 7.58 | 273 | 3.500 | 11332 | 13 | 7.58 | 273 |
| 4.500 | 01252 | 10 | 10.80 | 210 | 4.500 | 11270 | 10 | 10.80 | 210 | 4.500 | 01286 | 10 | 10.80 | 210 | 4.500 | 11334 | 10 | 10.80 | 210 |
| 5.5625 | 01253 | 7 | 14.63 | 147 | 5.5625 | 11272 | 7 | 14.63 | 147 | 5.5625 | 01324 | 7 | 14.63 | 147 | 5.5625 | 11335 | 7 | 14.63 | 147 |
| 6.625 | 01254 | 5 | 18.99 | 105 | 6.625 | 11273 | 5 | 18.99 | 105 | 6.625 | 01325 | 5 | 18.99 | 105 | 6.625 | 11336 | 5 | 18.99 | 105 |
| 8.625 | 01255 | 5 | 28.58 | 105 | 8.625 | 11274 | 5 | 28.58 | 105 | 8.625 | 01326 | 5 | 28.58 | 105 | 8.625 | 11337 | 5 | 28.58 | 105 |
| 10 | 01256 | 1 | 40.52 | 21 | | | | | | | | | | | | | | | |
| 12 | 01257 | 1 | 49.61 | 21 | | | | | | | | | | | | | | | |
| 14 | 01261 | 1 | 54.62 | 21 | | | | | | | | | | | | | | | |
| 16 | 69390 | 1 | 62.64 | 21 | | | | | | | | | | | | | | | |
| 18 | 01259 | 1 | 70.65 | 21 | | | | | | | | | | | | | | | |
| A53 Type E -Grade B Sch. 80 ERW | | | | | | | | | | | | | | | | | | | |
| NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft - 21' | | | | | | | | | | | | | | | |
| 2.375 | 02884 | 24 | 5.03 | 504 | | | | | | | | | | | | | | | |
| 2.875 | 02885 | 20 | 7.67 | 420 | | | | | | | | | | | | | | | |
| 3.500 | 01243 | 13 | 10.25 | 273 | | | | | | | | | | | | | | | |
| 4.500 | 02244 | 10 | 14.98 | 210 | | | | | | | | | | | | | | | |

Please note 42' lengths BLK PE come in the same pieces per lift as 21'.

FIRE SPRINKLER PIPE - 21' Lengths

| Sch. 40 ASTM A795E Black P.E. | | | | | A53 Type F Sch. 40 Black P.E. S-CUT | | | | | Mega-Thread ASTM A795E Black P.E. | | | | | MLT ASTM A795E Black Lightwall | | | | |
|----------------------------------|---------|---------------|--------|---------|-------------------------------------|---------|---------------|--------|---------|-----------------------------------|---------|---------------|--------|---------|-------------------------------------|---------|---------------|--------|---------|
| NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft |
| 1 | 21649 | 70 | 1.6800 | 1470 | 1 | 00357 | 70 | 1.6800 | 1470 | 1 | 70760 | 70 | 1.4620 | 1470 | 1 | 71205 | 91 | 1.3700 | 1911 |
| 1-1/4 | 21650 | 51 | 2.2700 | 1071 | 1-1/4 | 00358 | 51 | 2.2700 | 1071 | 1-1/4 | 70761 | 51 | 1.9890 | 1071 | 1-1/4 | 71206 | 61 | 1.8060 | 1281 |
| 1-1/2 | 21651 | 44 | 2.7200 | 924 | 1-1/2 | 00359 | 44 | 2.7200 | 924 | 1-1/2 | 70762 | 44 | 2.3700 | 924 | 1-1/2 | 71207 | 61 | 2.0850 | 1281 |
| 2 | 21652 | 30 | 3.6500 | 630 | 2 | 00360 | 30 | 3.6600 | 630 | 2 | 70763 | 30 | 3.0940 | 630 | 2 | 71208 | 37 | 2.6380 | 777 |
| SCHEDULE 10 ASTM A135 Black R.G. | | | | | SCHEDULE 10 ASTM A135 Galv R.G. | | | | | Megaflo ASTM A795E Black R.G. | | | | | WLS - SCH. 30 A795F Black P.E. | | | | |
| NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft |
| 1-1/4 | 41650 | 61 | 1.806 | 1281 | 1-1/4 | 71669 | 61 | 1.108 | 1281 | 1-1/4 | 71321 | 61 | 1.108 | 1281 | 1 | 00850 | 70 | 1.462 | 1470 |
| 1-1/2 | 41651 | 61 | 2.085 | 1281 | 1-1/2 | 71670 | 61 | 1.556 | 1281 | 1-1/2 | 71322 | 61 | 1.556 | 1281 | 1-1/4 | 00851 | 55 | 1.928 | 1155 |
| 2 | 41652 | 37 | 2.638 | 777 | 2 | 71662 | 37 | 1.961 | 777 | 2 | 71323 | 37 | 1.961 | 777 | 1-1/2 | 00852 | 45 | 2.369 | 945 |
| 2-1/2 | 41653 | 30 | 3.530 | 630 | 2-1/2 | 71663 | 30 | 2.504 | 630 | 2-1/2 | 71324 | 30 | 2.504 | 630 | 2 | 00853 | 35 | 3.003 | 735 |
| 3 | 41654 | 19 | 4.332 | 399 | 3 | 71664 | 19 | 3.349 | 399 | 3 | 71325 | 19 | 3.349 | 399 | GL ASTM A795E Galvanized Threadable | | | | |
| 4 | 41656 | 19 | 5.613 | 399 | 4 | 71665 | 19 | 4.331 | 399 | 4 | 71326 | 19 | 4.331 | 399 | NPS | Matl. # | Pcs. Per Lift | Wgt/Ft | Ftg/Lft |
| 5 | 41657 | 13 | 7.769 | 273 | 5 | 71667 | 13 | 7.769 | 273 | 6 | 71328 | 10 | 7.996 | 210 | 1 | 72205 | 91 | 1.3700 | 1911 |
| 6 | 41658 | 10 | 9.298 | 210 | 6 | 71658 | 10 | 9.298 | 210 | | | | | | 1-1/4 | 72206 | 61 | 1.7610 | 1281 |
| 8 | 41659 | 7 | 16.960 | 147 | 8 | 72089 | 7 | 16.960 | 147 | | | | | | 1-1/2 | 72207 | 61 | 2.0330 | 1281 |
| SCHEDULE 10 ASTM A135 Black P.E. | | | | | | | | | | | | | | | | | | | |
| NPS | Matl. # | Pcs. | Wgt/Ft | Ftg/Lft | | | | | | | | | | | | | | | |
| 1 | 31649 | 70 | 1.410 | 1470 | | | | | | | | | | | | | | | |

Standard Packaging Requirements - Contact your Customer Service Representative at 800-257-8182; website www.wheatland.com